

A standard linear barcode is positioned vertically on the right side of the page. It consists of vertical black bars of varying widths on a white background.

		Subclass	ISSUE CLASSIFICATION
--	--	----------	----------------------

U.S. UTILITY Patent Application

O.I.P.E.	PATENT DATE
 SCANNED <u>BKO</u> Q.A. <u>UK</u>	

APPLICATION NO.	CONT/PRIOR	CLASS	SUBCLASS	ART UNIT	EXAMINER
09/742560	F	052	649,1	3635	Stephan Yip

CANTS *Benito Zambelli*

Reinforcement for prefabricated concrete panels with improved bonding to concrete

PTO-2040
12/99

ISSUING CLASSIFICATION

TERMINAL DISCLAIMER		DRAWINGS			CLAIMS ALLOWED	
		Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.					NOTICE OF ALLOWANCE MAILED <hr/> <hr/> <hr/>	
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____ <hr/> <hr/>					ISSUE FEE <hr/> <hr/> <hr/>	
<input type="checkbox"/> The terminal _____ months of					Amount Due Date Paid	
					ISSUE BATCH NUMBER	

WARNING:

The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-436A
(Rev. 6/99)

FILED WITH: DISK (CRF) FICHE CD-ROM
(Attached in pocket on right Inside flap)